



RUBBER



IMPIEGO APPLICATIONS

Idoneo al trasporto a bassa pressione di prodotti abrasivi e fluidi in genere, in particolare betoncino, intonaco, gesso, ghiaia e malta.

Suitable for the low pressure transport of abrasive products and fluids in general. In particular for spraying plaster, grout, sand, sypsum, ready mixed concrete.



STRUTTURA BODY









A Sottostrato tube	Liscio in gomma nera antiabrasiva (nr/sbr). Abrasion resistant, antistatic natural rubber.
B Inserti Reinforcement	Tessili sintetici ad alta tenacità. High tensile synthetic textile.
C Copertura Cover	gomma nera antiabrasiva (nr/sbr) resistente agli agenti atmosferici. Abrasion, ozone and weather resistant pin-pricked natural and synthetic rubber.
Superficie Surface	Liscia ad impressione tela. Smooth with fabric impression.



FASCETTE E COLLARI STRINGITUBO CONSIGLIATE RECOMMENDED CLAMP/COLLAR

stc - fascette con bullone Hose clamps with bolt (pag. 212-214)



 mm	 mm	 bar	 bar	 bar	 gr/mt	 mm	 m
51	68	12	36	-	1968	508	40
50	70	12	36	-	2271	508	40
50	74	12	36	-	2800	508	40
60	80	12	36	-	2659	600	40
60	82	12	36	-	2720	600	40
63	84	12	36	-	2790	630	40
65*	84	12	36	-	2820	650	40
65*	85	12	36	-	2841	650	40



NORME NORMS:
ISO 1307

MARCATURA MARKING:
EUROCORD® ABRABETON W.P. 12 BAR

CONFEZIONAMENTO BOX:
IMBALLO IN POLIETILENE TRASPARENTE
PACKAGING IN TRANSPARENT POLYETHYLENE



-40°C / +70°C
-40°F / +158°F

* Versione 4 tele 4 plies Version