



**RUBBER**

**IMPIEGO APPLICATIONS**

Idoneo al trasporto a bassa pressione di prodotti abrasivi e fluidi in genere, in particolare betoncino, intonaco, gesso, ghiaia e malta.

Suitable for the low pressure transport of abrasive products and fluids in general. In particular for spraying plaster, grout, sand, sypsum, ready mixed concrete.



**STRUTTURA BODY**

<b>A</b> <b>Sottostrato tube</b>	Liscio in gomma nera antiabrasiva (nr/sbr). Abrasion resistant, antistatic natural rubber.
<b>B</b> <b>Inserti Reinforcement</b>	Tessili sintetici ad alta tenacità. High tensile synthetic textile.
<b>C</b> <b>Copertura Cover</b>	gomma nera antiabrasiva (nr/sbr) resistente agli agenti atmosferici. Abrasion, ozone and weather resistant pin-pricked natural and synthetic rubber.
<b>Superficie Surface</b>	Liscia ad impressione tela. Smooth with fabric impression.

mm	mm	bar	bar	bar	gr/mt	mm	m
20	31	40	120	-	360	200	60
25	37	40	120	-	683	254	60
30	42	40	120	-	930	300	60
30	45	40	120	-	1046	300	60
35	48	40	120	-	1136	350	60
40	55	40	120	-	1370	400	60
50	66	40	120	-	1746	508	60
50	68	40	120	-	1968	508	60
50	70	40	120	-	2271	508	60
50	74	40	120	-	2800	508	60

**FASCETTE E COLLARI STRINGITUBO CONSIGLIATE RECOMMENDED CLAMP/COLLAR**

stc - fascette con bullone Hose clamps with bolt (pag. 212-214)



**NORME NORMS:**  
ISO 1307

**MARCATURA MARKING:**  
EUROCORD® ABRABETON W.P. 40 BAR

**CONFEZIONAMENTO BOX:**  
IMBALLO IN POLIETILENE TRASPARENTE  
PACKAGING IN TRANSPARENT POLYETHYLENE

**-40°C / +70°C**  
**-40°F / +158°F**