



RUBBER

IMPIEGO APPLICATIONS

Idoneo per la mandata di carburanti senza piombo (EN 228:2017) e gasolio (EN 590:2017) per auto, camion e trattori. Adatto per B100 (100% biodiesel = RME), B20, B7 (EN 590:2017), E5 (EN 228:2017), E10, E85 e E100. Il rivestimento utilizzato soddisfa inoltre la RMA class A.

Suitable for the delivery of unleaded fuel (EN 228:2017) and diesel oils (EN 590:2017) for cars, trucks and tractors. Suitable for B100 (100% biodiesel = RME), B20, B7 (EN 590:2017), E5 (EN 228:2017), E10, E85 and E100. The used liner fulfills RMA class A.



STRUTTURA BODY

A	Sottostrato Tube	Gomma NBR di colore nero. Black NBR rubber.
B	Inserti Reinforcement	Tessili. Spiral textile.
C	Copertura Cover	Gomma nera liscia sintetica resistente ad ozono, abrasione e oli. Black and smooth syntetic rubber, ozone, abrasion and oil resistant.
	Superficie Surface	Liscia. Smooth.

mm	mm	bar	bar	bar	gr/mt	mm	m
5	11	12	36	-	95	30	50
6	12	12	36	-	120	36	50
7	13	12	36	-	130	42	50
8	14	12	36	-	150	48	50
10	16	12	36	-	200	60	50

FASCETTE E COLLARI STRINGITUBO CONSIGLIATE RECOMMENDED CLAMP/COLLAR

STF - Fascette a vite Hose clamps with screw (pag. 208-211)

STM - Fascette stringitubo Hose clamps (pag. 217)

SGT - Fascette pinzabili Stepp less (pag. 220)



NORME NORMS:
SAE J30R2 - SAE J30R6
MARCATURA MARKING:
EUROCORD® SAE J30 R2 SAE J30R6 W.P 12 BAR
CONFEZIONAMENTO BOX:
IMBALLO IN POLIETILENE ROSSO
PACKAGING IN RED POLYETHYLENE



-30°C / +100°C
-22°F / +212°F