



PVC



- **Resistenza alle alte temperature.**  
High temperature resistant.

**IMPIEGO APPLICATIONS**

Tubo in silicone trasparente idoneo alla mandata di liquidi alimentari secondo FDA (CFR 21 cap. 177.2600) ove richiesta resistenza ad alte temperature. Durezza 60 Sh A.

Transparent silicone hose suitable for the delivery of food liquids accordin to FDA (CFR 21 cap. 177.2600) where is necessary an high temperature resistance. Hardness 60 Sh A.



**STRUTTURA BODY**

<b>A</b>	<b>Materiale Material</b>	Silicone atossico. Neutral non toxical silicone hose.
<b>B</b>	<b>Inserti Reinforcement</b>	---
<b>C</b>	<b>Copertura Cover</b>	Silicone traslucido. Translucent silicone.
	<b>Superficie Surface</b>	Trasparente. Transparent.

mm	mm	bar	bar	bar	gr/mt	mm	m
2	4	-	-	-	12	-	100
3	5	-	-	-	16	-	100
3	6	-	-	-	26	-	100
4	6	-	-	-	20	-	100
4	7	-	-	-	32	-	100
4	8	-	-	-	46	-	100
5	8	-	-	-	38	-	100
5	9	-	-	-	54	-	100
5	10	-	-	-	75	-	100
6	8	-	-	-	27	-	100
6	9	-	-	-	45	-	100
6	10	-	-	-	62	-	100
6	12	-	-	-	103	-	100
7	10	-	-	-	51	-	50
7	11	-	-	-	69	-	50
8	10	-	-	-	37	-	50
8	12	-	-	-	77	-	50
8	13	-	-	-	101	-	50
8	14	-	-	-	127	-	50
9	12	-	-	-	63	-	50
10	14	-	-	-	92	-	50
10	16	-	-	-	111	-	50
12	16	-	-	-	112	-	50
12	18	-	-	-	177	-	50
14	18	-	-	-	123	-	50
15	20	-	-	-	172	-	50
18	24	-	-	-	247	-	25
22	26	-	-	-	194	-	25

**FASCETTE E COLLARI STRINGITUBO CONSIGLIATE RECOMMENDED CLAMP/COLLAR**

STF - Fascette a vite Hose clamps with screw (pag. 208-211)

SGT - Fascette pinzabili Stepp less (pag. 220)

SBS - Fascette bifilari a molla Double wire spring (pag. 217)



**NORME NORMS:**  
REG. UE 10/2011 FOR SIMULANT TYPE A-B-C  
ISO 1307

**DICHIARAZIONE DI CONFORMITÀ DISPONIBILE  
DECLARATION OF COMPLIANCE IS AVAILABLE**



**-60°C / +150°C**  
con picchi fino a  
with peaks up to  
**+200°C**

**-76°F / +302°F**  
con picchi fino a  
with peaks up to  
**+392°F**