


# L/RC

RIVESTIMENTO TAMBURI  
CON INSERTI IN CERAMICA 6x25x25

LAGGING FOR DRUMS with ceramic inserts 6x25x25



## IMPIEGO APPLICATIONS

Gomma antiabrasiva utilizzata comunemente come rivestimento di tamburi metallici nel settore dei nastri trasportatori.

Viene fornita con un lato in gomma cruda per la vulcanizzazione a freddo tramite soluzione specifica, la quale conferisce un eccezionale attacco gomma-metallo.

**Superficie:** Con inserti ceramici.

The coating for the drum with ceramic inserts is an ideal solution to increase the grip between the drum and the conveyor belt, remove slippage, expel water, reduce belt tension, lengthen the service life of the bearings, the joint and the coating of the drum itself, etc. increase energy services. The surfaces of the ceramic inserts have 18 embossed contact points to further increase the grip. It comes in 6x25x25 length strips and with the sub-layer prepared for bonding.

**Surface:** With ceramic inserts



## STOCK



mm

m

m

12

✓

0,500

5

12

--

0,500

10



## DUREZZA HARDNESS



## CARICO ROTTURA TENSILE STRENGTH



## ALLUNGAMENTO ELONGATION

Norme / Norms:  
ASTM D2240

Norme / Norms:  
ASTM D412

Norme / Norms:  
ASTM D412

70 Shore A ± 5

170 kg/cm<sup>2</sup>

450%



1,1 gr/cm<sup>3</sup>



-40°C / +70°C  
-40°F / +158°F