

L/T3

LÁMINA DE 30.000 VOLTIOS

30.000 VOLT FINE RIBBED MAT



- **Conforme a las Normas CEI EN 60243 -1.**
Complies with standards IEC EN 60243-1.



USO APPLICATIONS

Plancha de recubrimiento con dibujo de superficie mil rayas. Compuesto de caucho aislante con propiedades dieléctricas. Se utiliza habitualmente para cubrir suelos y pasarelas en centrales eléctricas, subestaciones eléctricas, naves industriales, etc. Conforme con las normas IEC EN 60243 -1.

Superficie: Mil rayas/I.T.

Mat with fine ribbed surface design. Mix of insulating rubber with dielectric properties. Commonly used to cover floors and walkways in electrical power stations, electricity cabins, industrial premises, etc. Complies with standards iec en 60243 -1.

Surface: Fine ribbed/I.T.



mm

3

STOCK

✓



m

1



m

10



DUREZA
HARDNESS

Norme / Norms:
ASTM D2240

70 Shore A ± 5

TENSIÓN DE PERFORACIÓN
PUNCTURE VOLTAGE

30.000 V

Declaración de conformidad disponible.
Declaration of compliance is available.



4,5 gr/cm³
peso específico / specific weight
1,5 gr/cm

-25°C / +80°C
-13°F / +176°F