



RUBBER



USO APPLICATIONS

Adecuada para entrega de fluidos hidráulicos, aceites minerales, lubricantes, gasóleo, gasolina.

Can be used as a fuel line. Suitable for the delivery of unleaded fuels and diesel oils especially in the automotive sectors.



ESTRUCTURA BODY

A Capa interior Tube	Caucho sintético de color negro. Black synthetic rubber.
B Refuerzos Reinforcement	1 trenza de hilo sintético de alta resistencia. 1 spiral textile.
C Capa exterior Cover	Caucho sintético resistente a los agentes atmosféricos, la abrasión, los aceites, óleo y carburantes. Black and smooth synthetic rubber, ozone, abrasion and oil resistant.
Superficie Surface	Lisa. Smooth.



ABRAZADERAS Y COLLARES DE APRIETE RECOMENDADOS RECOMMENDED CLAMP/COLLAR

STF - Abrazaderas de tornillo Hose clamps with screw (pag. 204-207)

STM - Abrazaderas de apriete Hose clamps (pag. 213)

SGT - Abrazaderas pinzables Stepp less (pag. 216)



mm	mm	bar	bar	bar	gr/mt	mm	m
5	11	10	30	-	95	50	100
6	12	10	30	-	120	60	100
7	13	10	30	-	130	70	100
8	14	10	30	-	150	80	100
10	16	10	30	-	200	100	100
13	20	10	30	-	290	130	50
16	24	10	30	-	352	160	50
19	27	10	30	-	405	190	50
25	35	10	30	-	660	250	50



NORMAS NORMS:
ISO 1307 - SAE J30 R7

MARCADOR MARKING:
EUROCORD® SAE J30 R7 FUEL HOSE

EMBALAJE BOX:
EMBALAJE EN POLIETILENO ROJO
PACKAGING IN RED POLYETHYLENE



-30°C / +120°C
-22°F / +248°F