

**PASO ESTRECHO
SHORT PITCH**



PVC



- **Excelente entrega y aspiración de líquidos alimentarios.**
Great suction and delivery of food liquids.
- **Versión superelástica.**
Super elastic version.

USO APPLICATIONS

Adecuada para entrega y la aspiración de líquidos alimentarios conforme con el Reglamento europeo n.º 10/2011 para los simulantes A-B-C. Especialmente indicada en la industria alimentaria, la agricultura y la industria para acompañar a las bombas de aspiración.

For suction and delivery of food liquids according to EU Regulation 10/2011 for A-B-C simulants. Particularly used in the food, agricultural and industrial sectors in support of suction pumps.



ESTRUCTURA BODY

A	Material	PVC flexible. Strong, very flexible and smooth non-toxic, transparent plasticized PVC.
B	Refuerzos Reinforcement	Espiral de acero incorporada en la pared de la manguera. Steel wire spiral incorporated in hose wall.
C	Capa exterior Cover	PVC transparente. Transparent PVC.
	Superficie Surface	Lisa, transparente. Smooth, transparent.

mm	mm	bar	bar	bar	gr/mt	mm	m
10	3,1	12	-	0,9	180	23	60
12	3,1	12	-	0,9	190	24	60
14	3,1	12	-	0,9	230	28	60
16	3,1	12	-	0,9	260	32	60
18	3,5	11	-	0,9	296	28	60
20	3,5	10	-	0,9	340	30	60
22	3,7	10	-	0,9	400	33	60
25	4,0	10	-	0,9	520	38	60
30	4,2	9	-	0,9	630	45	60
32	4,2	9	-	0,9	660	48	30
35	4,3	9	-	0,9	750	52	30
38	4,5	9	-	0,9	800	57	30
40	4,8	9	-	0,9	950	60	30
45	4,9	9	-	0,9	1150	67	30
50	5,4	7	-	0,9	1300	75	30
60	6,0	6	-	0,9	1750	120	30
63	6,1	6	-	0,9	1800	130	30
70	6,7	5	-	0,9	2100	140	30
80	6,3	4	-	0,8	2500	160	30
90	6,5	4	-	0,8	2900	180	30
100	7,5	3	-	0,8	3650	200	30
110	7,0	3	-	0,8	3950	220	20
120	8,0	3	-	0,8	4300	240	20
125	8,0	3	-	0,8	4600	250	20

ABRAZADERAS Y COLLARES DE APRIETE RECOMENDADOS
RECOMMENDED CLAMP/COLLAR

- STF - Abrazaderas de tornillo Hose clamps with screw (pag. 204-207)
- STC - Abrazaderas con perno Hose clamps with bolt (pag. 208-210)

NORMAS NORMS:
REG. UE 10/2011 FOR SIMULANT TYPE A-B-C
ISO 1307
DECLARACIÓN DE CONFORMIDAD DISPONIBLE
DECLARATION OF COMPLIANCE IS AVAILABLE

-5°C / +60°C
+23°F / +140°F