



PVC



**USO
APPLICATIONS**

Manguera de silicona transparente apta para entrega de líquidos alimentarios según la FDA (CFR 21 cap. 177.2600) cuando se requiere resistencia a altas temperaturas.

Transparent silicone hose suitable for the delivery of food liquids according to FDA (CFR 21 cap. 177.2600) where is necessary an high temperature resistance.



**ESTRUCTURA
BODY**

A	Material	Silicona no tóxica. Neutral non toxic silicone hose.
B	Refuerzos Reinforcement	---
C	Capa exterior Cover	Silicona translúcida. Translucent silicone.
	Superficie Surface	Transparente. Transparent.



**ABRAZADERAS Y COLLARES DE APRIETE
RECOMENDADOS
RECOMMENDED CLAMP/COLLAR**

- STF - Abrazaderas de tornillo Hose clamps with screw (pag. 204-207)
- SGT - Abrazaderas pinzables Stepp less (pag. 216)
- SBS - Abrazaderas bifilares con resorte Double wire spring (pag. 217)



- Resistencia a las altas temperaturas.**
High temperature resistant.



mm	mm	bar	bar	bar	gr/mt	mm	m
2	4	-	-	-	12	-	100
3	5	-	-	-	16	-	100
3	6	-	-	-	27	-	100
4	6	-	-	-	20	-	100
4	7	-	-	-	32	-	100
4	8	-	-	-	46	-	100
5	8	-	-	-	38	-	100
5	9	-	-	-	54	-	100
5	10	-	-	-	75	-	100
6	8	-	-	-	27	-	100
6	9	-	-	-	45	-	100
6	10	-	-	-	62	-	100
6	12	-	-	-	103	-	100
7	10	-	-	-	51	-	50
7	11	-	-	-	69	-	50
8	10	-	-	-	37	-	50
8	12	-	-	-	77	-	50
8	13	-	-	-	101	-	50
8	14	-	-	-	127	-	50
9	12	-	-	-	62	-	50
10	14	-	-	-	92	-	50
10	16	-	-	-	111	-	50
12	16	-	-	-	112	-	50
12	18	-	-	-	177	-	50
14	18	-	-	-	123	-	50
15	20	-	-	-	172	-	50
18	24	-	-	-	247	-	25
22	26	-	-	-	194	-	25



NORMAS NORMS:
REG. UE 10/2011 FOR SIMULANT TYPE A-B-
C ISO 1307

**DECLARACIÓN DE CONFORMIDAD DISPONIBLE
DECLARATION OF COMPLIANCE IS AVAILABLE**



-60°C / +150°C
con picos de hasta
with peaks up to
+200°C

-76°F / +302°F
con picos de hasta
with peaks up to
+392°F