



- **Excelente elongación.**
Great elongation.

RUBBER



USO APPLICATIONS

Manguito en caucho utilizado para transportar material a granel a la salida de la tolva (arena, cemento, grava, cereales).

Discharge of abrasive materials, such as sand, gravel, cement, grain and powder without pressure.



ESTRUCTURA BODY

A	Material	Manguera fabricada en mandril de NR (caucho natural) monocapa de color avellana claro. Abrasion resistant beige natural rubber.
B	Refuerzos Reinforcement	---
C	Superficie Surface	Lisa con impresión de tela. Smooth with fabric impression.
	Dureza Hardness	45 shore a ± 5
	Carga de rotura Breaking strenght	150 kg/cm ²
	Alargamiento a la rotura Breaking elongation	500%



ABRAZADERAS Y COLLARES DE APRIETE RECOMENDADOS RECOMMENDED CLAMP/COLLAR

STC - Abrazaderas con perno Hose clamps with bolt (**pag. 208-210**)



mm



mm



bar



gr/mt



mm



m

mm	mm	bar	gr/mt	mm	m
50 x 58	4	-	0,71	-	12
60 x 68	4	-	0,84	-	12
70 x 78	4	-	0,98	-	12
76 x 84	4	-	1,05	-	12
80 x 88	4	-	1,10	-	12
90 x 98	4	-	0,90	-	12
102 x 110	4	-	1,33	-	12
114 x 122	4	-	1,48	-	12
120 x 128	4	-	1,57	-	12
130 x 138	4	-	1,69	-	12
140 x 148	4	-	1,82	-	12
152 x 160	4	-	1,96	-	12
168 x 176	4	-	2,16	-	12
193 x 201	4	-	2,48	-	9
200 x 208	4	-	2,56	-	12
220 x 228	4	-	2,81	-	6
254 x 262	4	-	3,24	-	12
273 x 281	4	-	3,47	-	10
305 x 313	4	-	3,90	-	12
323 x 331	4	-	4,14	-	6
350 x 358	4	-	4,45	-	6
400 x 408	4	-	5,10	-	7
500 x 508	4	-	6,19	-	6
612 x 620	4	-	7,80	-	6



NORMAS NORMS:
ISO 1307

EMBALAJE BOX:
ROLLOS CORTADOS A MEDIDA
ROLLS CUT TO SIZE



-40°C / +70°C
-40°F / +158°F