

L/AA NBR

ANTIACEITE

OIL AND GREASE RESISTANT











- **Conforme a la lista de la FDA 177.2600 y a las normativas Europeas 1935/2004.**
It complies with the FDA list 177.2600.

USO APPLICATIONS


Cumple la norma FDA 177.2600 y las normas europeas 1935/2004. Especialmente adecuado en contacto con sustancias que contengan grasa.
Superficie: Lisa/Lisa o, a petición, I.T./I.T.


It complies with the FDA list 177.2600 and the European norm 1935/2004. In particular, it is suitable for contact with substances containing grease.
Surface: Smooth/Smooth or on request I.T./I.T.


 mm	STOCK	 m	 m
1	--	1,4	10
1,5	--	1,4	10
2 / 2,5	--	1,4	10
3 ÷ 10	--	1,4	10
12 ÷ 20	--	1,4	5
25 ÷ 50	--	1	1

 DUREZA HARDNESS	 CARGA DE ROTURA TENSILE STRENGTH	 ELONGACIÓN ELONGATION	 LACERACIÓN TEAR	 COMPRESSION > 22 h 70°C
Norme / Norms: ASTM D2240	Norme / Norms: ASTM D412	Norme / Norms: ASTM D412	Norme / Norms: ISO 34-1	Norme / Norms: ISO 815-1
65 Shore A ± 5	100 kg/cm ²	400%	>=20 N/mm	<=30%

Declaración de conformidad disponible.
Declaration of compliance is available.


1,4 gr/cm³


-25°C / +100°C
-13°F / +212°F