



RUBBER



USO APPLICATIONS

Manguera trenzada de acero inoxidable P.T.F.E. adecuada para sistemas hidráulicos, circuitos de lubricación, paso de carburante y vapores a altas temperaturas. Se utiliza especialmente en las industrias alimentaria, química y farmacéutica.

Stainless wire braided one-layer P.T.F.E hose suitable for hydraulic and lubricant system, fuel and steam high temperature delivery. Particularly suitable for food, chemical and pharmaceutical industries.



ESTRUCTURA BODY

A	Capa interior Tube	P.T.F.E. extruido. P.T.F.E one layer.
B	Refuerzos Reinforcement	Trenzado de alambre de acero inoxidable AISI 304. Stainless AISI 304 wire braid.
C	Capa exterior Cover	Trenzado de alambre de acero inoxidable AISI 304. Stainless AISI 304 wire braid.
	Superficie Surface	Trenzado. Braided.

3,8	1/8	6,2	-	1050	1	-	25	LONGITUD VARIABLE / VARIABLE SIZE
5	3/16	8	-	900	0,8	-	30	
6,5	1/4	9,5	-	820	0,8	-	45	
8,2	5/16	11,4	-	700	0,8	-	50	
10	3/8	13,2	-	550	0,8	-	60	
13,4	1/2	16,6	-	480	0,8	-	90	
16,4	5/8	20,2	-	410	1	-	125	
19,6	3/4	23,2	-	360	1	-	160	
22,2	7/8	26	-	280	1	-	220	
26	1	30	-	260	1,2	-	245	



NORMAS NORMS:
ISO 1307
EMBALAJE BOX:
EMBALAJE DE CARTÓN
CARTON BOXES



-70°C / +260°C
-94°F / +500°F