



**RUBBER**



**USO APPLICATIONS**

Manguera convoluta trenzada de acero inoxidable P.T.F.E. adecuada para sistemas hidráulicos, circuitos de lubricación, carburante y paso de vapores a alta temperatura. Se utiliza especialmente en las industrias alimentaria, química y farmacéutica.

Stainless wire braided one-layer P.T.F.E convoluted hose suitable for hydraulic and lubricant system, fuel and steam high temperature delivery. Particularly suitable for food, chemical and pharmaceutical industries.



**ESTRUCTURA BODY**

<b>A</b>	<b>Capa interior Tube</b>	P.T.F.E. corrugado. Convoluted P.T.F.E.
<b>B</b>	<b>Refuerzos Reinforcement</b>	Trenzado de alambre de acero inoxidable AISI 304. Stainless AISI 304 wire braid.
<b>C</b>	<b>Capa exterior Cover</b>	Trenzado de alambre de acero inoxidable AISI 304. Stainless AISI 304 wire braid.
	<b>Superficie Surface</b>	Trenzado. Braided.

6	1/4	10,6	-	800	0,7	-	18	LONGITUD VARIABLE VARIABLE SIZE
7,5	5/16	14	-	650	0,7	-	19	
9,7	3/8	16,4	-	500	0,7	-	20	
13	1/2	19	-	309	0,7	-	25	
15,5	5/8	21	-	350	0,8	-	50	
19,6	3/4	26	-	250	0,8	-	64	
24,4	1	33,7	-	200	1	-	90	
32,5	1 1/4	40,3	-	170	1	-	110	
38	1 1/2	48,4	-	120	1	-	150	
50,9	2	61,4	-	100	1,1	-	190	



**NORMAS NORMS:**  
ISO 1307  
**EMBALAJE BOX:**  
EMBALAJE DE CARTÓN  
CARTON BOXES



**-70°C / +260°C**  
**-94°F / +500°F**