



USU APPLICATIONS

Nautica Alimentación Marine Food

DESCRIPCIÓN DESCRIPTION

Abrazadera de alta estanqueidad, compacta y resistente. La banda interior lisa y los bordes elevados confieren a la manguera una seguridad absoluta. Conforme con la normativa DIN 3017.

High resistant clamp, compact and durable. Rolled-up band edges and smooth band underside are able to guarantee total protection to the hose. Conforme to DIN 3017.

MATERIAL MATERIAL

Banda Band	Acero inoxidable Stainless steel AISI 304
Cajón Housing	Acero inoxidable Stainless steel AISI 304
Tornillo Screw	Acero inoxidable Stainless steel AISI 304

	ANCH. CINTA BAND WIDTH	DIÁM. DIAM.	ESPESOR THICKNESS	PAR DE APRIETE RECOMENDADO (PÁG. 221)	CAJAS BOX	
	A mm	B mm	C mm	Nm	pz/nrm	
9 mm	W4A09008012000	9	8-12	0,8	2,6	100
	W4A09010016000	9	10-16	0,8	2,6	100
	W4A09012020000	9	12-20	0,8	2,6	100
	W4A09016025000	9	16-25	0,8	4,0	100
	W4A09016027000	9	16-27	0,8	4,0	100
	W4A09020032000	9	20-32	0,8	4,0	100
	W4A09025040000	9	25-40	0,8	4,0	100
	W4A09035050000	9	32-50	0,8	4,0	50
	W4A09040060000	9	40-60	0,8	4,0	50
	W4A09050070000	9	50-70	0,8	4,0	50
	W4A09060080000	9	60-80	0,8	4,0	50
	W4A09070090000	9	70-90	0,8	4,0	25
	W4A09080100000	9	80-100	0,8	4,0	25
	W4A09090110000	9	90-110	0,8	4,0	25
	W4A09100120000	9	100-120	0,8	4,0	25
	W4A09110130000	9	110-130	0,8	4,0	25
W4A09120140000	9	120-140	0,8	4,0	25	
W4A09130150000	9	130-150	0,8	4,0	25	
12 mm	W4B12012020000	12	12-20	1,0	6,5	100
	W4B12016025000	12	16-25	1,0	6,5	100
	W4B12016027000	12	16-27	1,0	6,5	100
	W4B12020032000	12	20-32	1,0	6,5	100
	W4B12025040000	12	25-40	1,0	6,5	100
	W4B12035050000	12	32-50	1,0	6,5	50
	W4B12040060000	12	40-60	1,0	6,5	50
	W4B12050070000	12	50-70	1,0	6,5	50
	W4B12060080000	12	60-80	1,0	6,5	50
	W4B12070090000	12	70-90	1,0	6,5	25
	W4B12080100000	12	80-100	1,0	6,5	25
	W4B12090110000	12	90-110	1,0	6,5	25
	W4B12100120000	12	100-120	1,0	6,5	25
	W4B12110130000	12	110-130	1,0	6,5	25
	W4B12120140000	12	120-140	1,0	6,5	25
	W4B12130150000	12	130-150	1,0	6,5	25
W4B12140160000	12	140-160	1,0	6,5	25	
W4B12150170000	12	150-170	1,0	6,5	25	
W4B12160180000	12	160-180	1,0	6,5	25	
W4B12170190000	12	170-190	1,0	6,5	25	
W4B12180200000	12	180-200	1,0	6,5	25	