



**USO APPLICATIONS**

Náutica Marine  
 Petroquímica Petrochemical  
 Alimentación Food

**DESCRIPCIÓN DESCRIPTION**

Abrazadera de alta estanqueidad, compacta y resistente. La banda interior lisa y los bordes elevados confieren a la manguera una seguridad absoluta. Conforme con la normativa DIN 3017.

High resistant clamp, compact and durable. Rolle-up band edges and smooth band underside are able to guarantee total protection to the hose. Conforme to DIN 3017.

**MATERIAL MATERIAL**

<b>Banda Band</b>	Acero inoxidable Stainless steel <b>AISI 316</b>
<b>Cajón Housing</b>	Acero inoxidable Stainless steel <b>AISI 316</b>
<b>Tornillo Screw</b>	Acero inoxidable Stainless steel <b>AISI 316</b>

ANCH. CINTA BAND WIDTH	DIÁM. DIAM.	ESPESOR THICKNESS	PAR DE APRIETE RECOMENDADO TORQUE (PAG. 221)	CAJAS BOX
<b>A</b>	<b>B</b>	<b>C</b>	<b>Nm</b>	<b>pz/nrm</b>

<b>9</b> mm	<b>W5A09008012000</b>	9	8-12	0,8	2,6	100
	<b>W5A09010016000</b>	9	10-16	0,8	2,6	100
	<b>W5A09012020000</b>	9	12-20	0,8	2,6	100
	<b>W5A09016025000</b>	9	16-25	0,8	4,0	100
	<b>W5A09016027000</b>	9	16-27	0,8	4,0	100
	<b>W5A09020032000</b>	9	20-32	0,8	4,0	100
	<b>W5A09025040000</b>	9	25-40	0,8	4,0	100
	<b>W5A09035050000</b>	9	32-50	0,8	4,0	50
	<b>W5A09040060000</b>	9	40-60	0,8	4,0	50
	<b>W5A09050070000</b>	9	50-70	0,8	4,0	50
	<b>W5A09060080000</b>	9	60-80	0,8	4,0	50
	<b>W5A09070090000</b>	9	70-90	0,8	4,0	25
	<b>W5A09080100000</b>	9	80-100	0,8	4,0	25
	<b>W5A09090110000</b>	9	90-110	0,8	4,0	25
	<b>W5A09100120000</b>	9	100-120	0,8	4,0	25
<b>W5A09011013000</b>	9	110-130	0,8	4,0	25	
<b>W5A09012014000</b>	9	120-140	0,8	4,0	25	
<b>W5A09013015000</b>	9	130-150	0,8	4,0	25	
<b>12</b> mm	<b>W5B12012020000</b>	12	12-20	1,0	6,5	100
	<b>W5B12016025000</b>	12	16-25	1,0	6,5	100
	<b>W5B12016027000</b>	12	16-27	1,0	6,5	100
	<b>W5B12020032000</b>	12	20-32	1,0	6,5	100
	<b>W5B12025040000</b>	12	25-40	1,0	6,5	100
	<b>W5B12035050000</b>	12	32-50	1,0	6,5	50
	<b>W5B12040060000</b>	12	40-60	1,0	6,5	50
	<b>W5B12050070000</b>	12	50-70	1,0	6,5	50
	<b>W5B12060080000</b>	12	60-80	1,0	6,5	50
	<b>W5B12070090000</b>	12	70-90	1,0	6,5	25
	<b>W5B12080100000</b>	12	80-100	1,0	6,5	25
	<b>W5B12090110000</b>	12	90-110	1,0	6,5	25
	<b>W5B12100120000</b>	12	100-120	1,0	6,5	25
	<b>W5B12110130000</b>	12	110-130	1,0	6,5	25
	<b>W5B12120140000</b>	12	120-140	1,0	6,5	25
	<b>W5B12130150000</b>	12	130-150	1,0	6,5	25
	<b>W5B12140160000</b>	12	140-160	1,0	6,5	25
	<b>W5B12150170000</b>	12	150-170	1,0	6,5	25
<b>W5B12160180000</b>	12	160-180	1,0	6,5	25	
<b>W5B12170190000</b>	12	170-190	1,0	6,5	25	
<b>W5B12180200000</b>	12	180-200	1,0	6,5	25	