



**RUBBER**



**USO APPLICATIONS**

Adecuada para entrega y la aspiración de pinturas cuyos disolventes no contengan hidrocarburos aromáticos, clorados ni halogenados.

Suitable for delivery and suction of paints with solvents non containing aromatic, aliphatic and chlorinated hydrocarbons.



**ESTRUCTURA BODY**









<b>A</b> <b>Capa interior Tube</b>	Caucho liso negro resistente a la pintura. Black, smooth, paints resistant special rubber.
<b>B</b> <b>Refuerzos Reinforcement</b>	Espiral metálica incorporada y tejidos textiles sintéticos de alta resistencia. Steel wire helix with high strength synthetic textile plies.
<b>C</b> <b>Capa exterior Cover</b>	Caucho negro resistente a la abrasión, la pintura, el ozono y los agentes atmosféricos. Black, abrasion, paints, weathering and ozone, resistant rubber.
<b>Superficie Surface</b>	Lisa con impresión de tela. Smooth with fabric impression.



**ABRAZADERAS Y COLLARES DE APRIETE RECOMENDADOS RECOMMENDED CLAMP/COLLAR**

STC - Abrazaderas con perno Hose clamps with bolt (pag. 208-210)  
BANDI BLOCK - Par de apriete Tightening torque (pag. 221)



 mm	 mm	 bar	 bar	 bar	 gr/mt	 mm	 m
13	23	10	15	0,8	450	55	40
16	26	10	15	0,8	500	65	40
19	30	10	15	0,8	600	75	40
25	36	10	15	0,8	750	100	40



**NORMAS NORMS:**  
ISO 1307 - ISO 22241-2  
**MARCADOR MARKING:**  
EUROCORD® VERNICI/SP

**EMBALAJE BOX:**  
EMBALAJE EN POLIETILENO TRANSPARENTE  
PACKAGING IN TRANSPARENT POLYETHYLENE



**-40°C / +100°C**  
**-40°F / +212°F**