

L/T5

LASTRA 50.000 VOLT

50.000 VOLT FINE RIBBED MAT



- **Conforme alle norme IEC EN 60243-1.**
Complies with standards IEC EN 60243-1.



IMPIEGO APPLICATIONS

Tappeto con disegno in superficie millerighe. Mescola in gomma isolante con proprietà dielettriche. Utilizzata comunemente per ricoprire pavimentazioni e passatoie di centrali elettriche, cabine elettriche, locali industriali ecc.

Conforme alle norme IEC EN 60243 -1.

Superficie: Millerighe/I.T.

Mat with fine ribbed surface design. Mix of insulating rubber with dielectric properties. Commonly used to cover floors and walkways in electrical power stations, electricity cabins, industrial premises, etc.

Complies with standards IEC EN 60243 -1..

Surface: Fine ribbed/I.T.



STOCK



mm

m

m

4,5

✓

1

10



DUREZZA
HARDNESS

TENSIONE DI PERFORAZIONE
PUNCTURE VOLTAGE

Norme / Norms:
ASTM D2240

70 Shore A ± 5

50.000 V

Dichiarazione di conformità disponibile.

Declaration of compliance is available.



6,40 gr/cm³
peso specifico / specific weight
1,5 gr/cm

-25°C / +80°C
-13°F / +176°F